

XBlack

XB350

10,000 OUTPUT LUMENS

HYBRID PERFORMANCE MOVING HEAD WASH LIGHT

PROFILE | BEAM | WASH | HYBRID



LATEST GENERATION
TECHNOLOGY FOR ULTIMATE
PERFORMANCE

USING THE LATEST GENERATION LED
ENGINE, LENS, FRAMING SYSTEM AND ZOOM
RATIO COMBINATION FOR MAXIMUM LIGHT
OUTPUT AND CONTROL.



TECHNICAL SPECIFICATIONS

OPTICAL

- SOURCE: 350 WATT WHITE LED ENGINE
 - OUTPUT: 10,000 LUMENS
 - COLOR TEMPERATURE: 2700K - 7500K
 - ZOOM RANGE: 3° - 48° LINEAR ZOOM
 - MINIMUM LED LIFESPAN: 20,000 HOURS
-

ELECTRICAL

- INPUT RANGE (AC 100-240V 50/60HZ)
 - MAX CONSUMPTION: 420 WATTS
-

DYNAMIC EFFECTS

- PAN 540° / 630° (16 BIT)
 - TILT 270° (16 BIT)
 - DIMMER: 0-100% ELECTRONIC LINEAR DIMMING (16 BIT)
 - STROBE: 1-25HZ, SYNCHRONIZED / RANDOM
 - IRIS: 5-100% ELECTRONIC IRIS
 - FROST: HEAVY FROST
 - PRISM 1: 5 FACET CIRCULAR, ROTATING, BI-DIRECTIONAL
 - PRISM 2: 5 FACET LINEAR, ROTATING, BI-DIRECTIONAL (OVERLAY)
 - COLOR: FULL CMY COLOR MIXING
 - COLOR WHEEL WITH 8 DICHROIC COLORS + OPEN
 - VARIABLE LINEAR CTO COLOR TEMPERATURE 2700K-7500K
 - ROTATING GOBO WHEEL WITH 7 GOBOS (16 BIT)
 - STATIC GOBO WHEEL WITH 10 GOBOS
-

CONTROL/CONNECTION

- DMX
 - RDM
 - ARTNET (RJ45)
 - CONTROL MODES: 25 CHANNEL (BASIC) / 36 CHANNEL (EXTENDED)
 - LCD DISPLAY WITH ONBOARD CONTROL PANEL
 - DATA INPUT/OUTPUT: 5 PIN DMX
 - POWER INPUT/OUTPUT: TRUE1
-

PHYSICAL

- IP20 INDOOR RATED
 - WEIGHT : 41LBS
 - DIMENSIONS: 23.5" X 14.4" X 8.26"
-

COOLING

- ADVANCED COOLING SYSTEM: USES SELF ADJUSTING AND VARIABLE SPEED FANS.